


Evolution XPC OFC Digital 110 Ohm AES/EBU 4 Pair



Product overview

Part number	300-304
Product description	Evolution XPC OFC Digital 110 Ohm AES/EBU 4 Pair

Cable construction

Conductor	Pair: 7 x 0.20mm 24 AGW pure OFC copper Drain: 7 x 0.20mm 24 AGW pure tinned copper
Insulation	Material: Foam PE Colour: Blue & White
Screen	Spiral pure OFC copper 100% coverage
Jacket	Supple grey PVC 3.6 mm OD Material: Abrasion resistant matt PVC compound Colour: Deep Purple Diameter: 10.80 mm
Marking	Evolution XPC OFC Digital 110 Ohm AES/EBU 4 Pair 300-304
Reel Length	100m, 500m
Weight	11 Kg/100m

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Direct Cable Systems Ltd

Unit 4 Parkbury Estate, Handley Page Way, Colney Street, St Albans, Hertfordshire AL2 2DQ, United Kingdom.
tel. +44 (0)208 238 7800 fax. +44 (0)208 238 7801 email. sales@directcablesystems.com Registered in UK No. 3409274



Electrical characteristics at 20°C

Conductor Resistance	69 Ω /Km @ 20°C
Rated Temperature (°C)	-30°C + 70 °C
Capacitance Core/Core	46 (pF/m)

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Direct Cable Systems Ltd

Unit 4 Parkbury Estate, Handley Page Way, Colney Street, St Albans, Hertfordshire AL2 2DQ, United Kingdom.
tel. +44 (0)208 238 7800 fax. +44 (0)208 238 7801 email. sales@directcablesystems.com Registered in UK No. 3409274

