

Evolution XPC OFC Digital 110 Ohm AES/EBU 12 Pair



Product overview

Part number	300-312
Product description	Evolution XPC OFC Digital 110 Ohm AES/EBU 12 Pair

Cable construction

Conductor	Pair: 7 x 0.203 mm Pure OFC copper 24AWG Drain: 7 x 0.20mm 24 AWG pure tinned copper
Insulation	Foam-Skin PE
Screen	Aluminium foil 100% coverage
Sheath	Flexible matt black abrasion resistant PVC Diameter: 17.40 mm
Jacket	Supple purple PVC Din spaced numbers 3.0 mm Colour: Black
Marking	Evolution XPC OFC Precision Digital 110 Ohm AES-EBU 12 Pair 300-012

Electrical characteristics at 20°C

DC resistance	85 Ω/Km @ 20°C
---------------	----------------

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Direct Cable Systems Ltd

Unit 4 Parkbury Estate, Handley Page Way, Colney Street, St Albans, Hertfordshire AL2 2DQ, United Kingdom.
tel. +44 (0)208 238 7800 fax. +44 (0)208 238 7801 email. sales@directcablesystems.com Registered in UK No. 3409274



Mutual capacitance 53.4803 pF/m

Characteristic impedance 110 Ω

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Direct Cable Systems Ltd

Unit 4 Parkbury Estate, Handley Page Way, Colney Street, St Albans, Hertfordshire AL2 2DQ, United Kingdom.
tel. +44 (0)208 238 7800 fax. +44 (0)208 238 7801 email. sales@directcablesystems.com Registered in UK No. 3409274

