

Evolution XPC OFC 1 Pair Heavy Duty



Product overview

Part number	301-031HD, 301-034HD
Product description	Evolution XPC OFC 1 Pair Heavy Duty

Cable construction

Conductor	1 Pair : Stranding 16 x 0.2 mm 20 AWG ,pure OFC copper tinned 2 Pair : Stranding 16 x 0.2 mm 20 AWG, pure OFC copper tinned
Insulation	Material : PVC Colour : - Blue & Red - Black & White
Shield	• Layer 1 Aluminium Polyester Tape, Coverage 100% • Drain Wire 0.5 mm 16 x 0.2 mm, pure OFC copper tinned
Jacket	Material : Flexible Abrasion Resistant PVC Compound • Diameter: 1 Pair: 5.1 mm 2 Pair: 8 mm • Jacket Matt Colour: Black
Marking	Evolution XPC OFC 1 Pair HD 301-031 HD Evolution XPC OFC 2 Pair HD 301-034HD
Reel lengths	100 m / 200 m / 500 m
Weight:	8.5 kg/100 m

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Electrical characteristics at 20°C

Resistance	38Ω/Km
Capacitance (pF/m)	100 pF/m core to core 190 pF/m Core/Screen
Operating temp	-20°C to + 70°C

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.