

Evolution XPC OFC high definition speaker cable



Product overview

Part number	301-056, 301-057, 301-058
Product description	Evolution XPC OFC high definition speaker cable

Cable construction

Conductor	Stranding: 2.5 mm ² : Pure OFC copper 7 x 46 x 0.1 mm 4.0 mm ² : Pure OFC copper 7 x 73 x 0.1 mm 6.0 mm ² : Pure OFC copper 7 x 3 x 37 x 0.1 mm
Insulation	Material: Transparent PVC Insulation Colour Transparent, directional/ identification stripe on one core
Jacket	Diameter : 2.5 mm : 12 x 4 mm 4.0 mm : 14 x 5 mm 6.0 mm : 16 x 6 mm Colour : Black
Marking	Evolution XPC OFC Professional 2 x 2.5 mm High Definition Speaker Cable 301-056 Evolution XPC OFC Professional 2 x 4.0 mm High Definition Speaker Cable 301-057 Evolution XPC OFC Professional 2 x 6.0 mm High Definition Speaker Cable 301-058
Reel lengths	100 m

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.

Weight	2.5 mm : 9 kg/100 m
	4.0 mm : 13.5 kg/100 m
	6.0 mm : 17.5 kg/100 m

Electrical characteristics at 20°C

Conductor Resistance	2.5 mm : 7.8 Ω /Km
	4.0 mm : 5.0 Ω /Km
	6.0 mm : 3.0 Ω /Km

Operating temp	-20°C to +90°C
-----------------------	----------------

Specifications subject to change without notice. Please contact Direct Cable Systems to verify information.